01785 247575
sales@morganrushworth.com
www.morganrushworth.com

MORGAN RUSHWORTH SBR 1550.110 POWERED BENDING ROLLERS



The Morgan Rushworth SBR Powered Bending Rolls have a rugged, heavy duty, cast iron frame ensuring a long working life and are used for applications up to a maximum material thickness of 5.5mm, subject to the individual model capacity. The asymmetric design provides pre-bending capability on the machine and the top slip roll allows removal of cylindrical components.

01785 247575
sales@morganrushworth.com
www.morganrushworth.com

FEATURES

- Powered top and bottom rolls with foot operated forward and reverse control
- Induction hardened rolls
- Braked motor
- Cast iron end frames
- Manual pinching of bottom roll
- Manual handwheel adjustment of the pre-bending roll
- Top slip roll for removal of complete cylinders
- Cone bending device
- Wire grooves

OPTIONS

- Powered back roll
- Digital read out for back roll position

TECHNICAL INFORMATION

MODEL		SBR 1550.110
Bending Length	mm	1550
Rolling Capacity	mm	3.5
Pre-Bending Capacity	mm	3.0
Top Roll Diameter	mm	110
Motor Power	kW	2.2
Length	mm	2320
Width	mm	850
Height	mm	1150
Weight	Kg	1250

OTHER IMAGES



