
MORGAN RUSHWORTH DPBH-4 2550.400 HYDRAULIC 4-ROLL PLATE BENDING ROLLS

The DPBH-4 hydraulic bending rolls are available with roll diameters ranging from 280mm up to the large 680mm machines. The 4 roll design is extremely powerful, with 3 of the rolls hydraulically driven and the fourth lower roll hydraulically adjusted up and down to pinch the material into position. This feature greatly assists the operator, especially during multiple radius bending as the work piece is always held. All models have hydraulic drop end and are supplied with DRO to all three adjusting rolls to indicate roll position.

FEATURES

- Hydraulic driven rolls.
- Hydraulic drop end and top roll tilt.
- Hydraulic up and down roll movement.
- Hydraulic pinching.
- Induction hardened rolls.
- DRO for both side rollers.
- Double pre bending to front and rear edge of plate.
- Cone bending device.
- Welded steel construction.
- Safety trip wire around the machine.
- Mobile control panel.
- Two speed.
- Central lubrication system.

OPTIONS

- Side and central sheet supports.
- Ground and polished rolls.
- Variable speed.
- NC controller.
- CNC controller.

TECHNICAL INFORMATION

MODEL		DPBH-4 2550.400
Bending Length	mm	2550
Pre Bending	mm	30
Max Thickness	mm	40
Top/Bottom Roll Dia	mm	400
Side Rolls Dia	mm	300
Motor	kW	38.5
Length	mm	5700
Width	mm	2320
Height	mm	2300
Weight	Kg	17950

OTHER IMAGES

