

---

**MORGAN RUSHWORTH PBXS CNC 3100.240 HYDRAULIC PRESS BRAKE**

The Morgan Rushworth PBXS CNC press brakes are fitted with the ESA VIS-875W CNC control featuring a 21" touch screen and both numerical and 2D graphical program entry. Bending can also be graphically visualised in 2D or 3D showing the machine frame, top and bottom tools, back gauge fingers and part orientation. PC based software is included and, with the control networked, can be used to load programs from the office. The PBXS CNC models feature 5 axis CNC control of the left and right ram cylinders, the back gauge depth, back gauge height and the bottom tool crowning system. The position of the two cylinders is fully synchronised with high precision scales on the side frames ensuring ram parallelism. These machines follow a rigorous design and manufacturing process to ensure minimum deflection of the machine frame under maximum working pressure. AKAS laser tooling guards are standard and offer a vastly improved operator experience without compromising safety.

All PBXS CNC models are supplied with sectionalised euro style top tools and a multi vee bottom die. The range covers models from 40 tonnes through to 1000 tonnes capacity with bending lengths from 1250mm up to 8100mm in the standard design. Special models can be built with larger widths and higher tonnages or for use as tandem machines. A comprehensive range of options are available to fully tailor the machine to requirements including 6-axis or 8-axis configurations.

## FEATURES

- ESA VIS-875W multi-axis CNC control with numerical and 2D graphical programming and 2D or 3D visualisation, mounted on pendant arm
- Fully synchronised CNC control of left and right upper beam cylinder position – Y1 + Y2 axis
- CNC control of back gauge depth – X axis
- CNC control of back gauge height – R axis
- CNC bottom tool crowning system - A axis
- Manual side to side movement of back gauge fingers – Z axis
- Quick release top tool clamping system
- Euro style top tool holders with intermediates including wedges for crowning
- Sectionalised goose neck top tool and multi vee bottom die
- Bottom tool wedge crowning system
- AKAS laser tooling guards for enhanced ease of use
- Strong rigid welded mono block frame able to withstand deflection under maximum load
- High precision linear scales for measurement of the stroke depth which are mounted on the side frames rather than the top beam to prevent any inaccuracy through distortion as the beam comes under load
- Hydraulic ram travel guided in low friction slide ways
- Large open height and generous ram stroke
- Deep reinforced throat in side frames
- High approach and return speeds for production bending
- Front support arms with flip stop, adjustable on a linear rail
- Dual foot switch console with emergency stop
- Electrically interlocked side guards
- Electrically interlocked rear access door

## OPTIONS

- Optional offline ESA Bend 3D Software with Control Viewer
- Independent CNC control of side to side movement of back gauge fingers – Z1 + Z2 axis
- Independent CNC tower back gauge system – X1 + R1 + Z1, X2 + R2 + Z2
- Laser angle measurement system with live feedback to CNC control
- Manual bottom tool crowning system with position counter
- Hydraulic top and bottom tool clamping system
- Additional back gauge fingers
- Additional front support arms
- Brush table for front support arms
- CNC sheet follower support arms
- Parking area for sheet follower support arms – one per side

## TECHNICAL INFORMATION

| MODEL                             | PBXS CNC 3100.240 |        |
|-----------------------------------|-------------------|--------|
| Bending Power                     | tonne             | 240    |
| Bending Length (Over Tooling)     | mm                | 3100   |
| Bending Length (Between Frames)   | mm                | 2550   |
| Y Axis Approach Speed             | mm/sec            | 130    |
| Y Axis Bending Speed (Maximum)    | mm/sec            | 10     |
| Y Axis Return Speed               | mm/sec            | 120    |
| X Axis Travel                     | mm                | 750    |
| X Axis Speed                      | mm/sec            | 350    |
| R Axis Travel                     | mm                | 160    |
| R Axis Speed                      | mm/sec            | 240    |
| No of Back Gauge Fingers          |                   | 2      |
| No of Sheet Support Arms          |                   | 2      |
| Stroke                            | mm                | 260    |
| Daylight                          | mm                | 530    |
| Throat Depth                      | mm                | 500    |
| Table Height                      | mm                | 880    |
| Table Width                       | mm                | 90     |
| Oil Capacity                      | litre             | 210    |
| Motor Power                       | kW                | 22.0   |
| Nominal Power (excluding options) | kW                | 26     |
| Length                            | mm                | 3850   |
| Width                             | mm                | 1950   |
| Height                            | mm                | 2905   |
| Weight                            | kg                | 11,400 |

OTHER IMAGES

