

---

**MORGAN RUSHWORTH HSP 95 HYDRAULIC PUNCHING MACHINE**

The Morgan Rushworth hydraulic punching machines are available in models from 70 tonne up to 175 tonne capacity. All models are equipped with a 625mm deep throat as standard. The heavy-duty support table with adjustable backstop, universal die holder for the punching of plate, flat bar, angle iron and flange of channel and beam are all included in the standard execution. The punching machines are also available in double-ended configuration. The standard machine allows punching of up to 57mm diameter without additional equipment. The front section of the support table can be removed in order to punch angle-iron leg down. A wide range of options are available including bar bending, sheet bending and corner notching.

## FEATURES

- Full stroke adjustment
- Low power inching
- Punch table with multipurpose bolster
- Removable table block for overhang channel/beam flange punching
- Low maintenance
- Overload relief on hydraulic system
- Swing away punch stripper unit
- Easy change punch holder
- Punch table with guides
- Work station guard
- Magnetic based working lamp

## OPTIONS

- Large hole attachments
- Bending units
- Special tooling & accessories

## TECHNICAL INFORMATION

MODEL		HSP 95
Punching		
Diameter X Maximum Thickness	mm	33 x 20
Maximum Diameter X Thickness	mm	57 x 12
Stroke Length	mm	80
Throat Depth	mm	625
Largest Hole Diameter - Standard	mm	57
Largest Hole Diameter (Optional)	mm	110
Tube Notch (Optional)		
Maximum Outside Diameter	mm	108
Bending (Optional)		
Bar Bending - Maximum Capacities	mm	250 x 20
Sheet Bending - Maximum Capacities	mm	500 x 3
Corner Notching (Optional)		
Maximum Capacity	mm	250 x 6
Technical Data		
Motor Power	kW	7.5
Length	mm	1850
Width	mm	950
Height	mm	1920
Weight	kg	3270

OTHER IMAGES

