

MORGAN RUSHWORTH HSP 50 HYDRAULIC PUNCHING MACHINE

The Morgan Rushworth hydraulic punching machines are available in models from 50 tonne up to 175 tonne capacity. All models are equipped with a 625mm deep throat as standard, except the 50 tonne model which is 300mm. The heavy-duty support table with adjustable backstop, universal die holder for the punching of plate, flat bar, angle iron and flange of channel and beam are all included in the standard execution. The punching machines are also available in double-ended configuration. The front section of the support table can be removed in order to punch angle-iron leg down. A wide range of options are available including bar bending, sheet bending and corner notching.

FEATURES

- Full stroke adjustment
- Low power inching
- Punch table with multipurpose bolster
- Removable table block for overhang channel/beam flange punching
- Low maintenance
- Overload relief on hydraulic system
- Swing away punch stripper unit
- Easy change punch holder
- Punch table with guides
- Work station guard
- Magnetic based working lamp

OPTIONS

- Large hole attachments
- Bending units
- Special tooling & accessories



TECHNICAL INFORMATION

MODEL	HSP 50	
Punching		
Diameter X Maximum Thickness	mm	24 x 15
Maximum Diameter X Thickness	mm	38 x 9
Stroke Length	mm	60
Throat Depth	mm	300
Largest Hole Diameter - Standard	mm	38
Largest Hole Diameter (Optional)	mm	110
Bending (Optional)		
Bar Bending - Maximum Capacities	mm	110 x 12
Technical Data		
Motor Power	kW	4.0
Length	mm	938
Width	mm	900
Height	mm	1666
Weight	kg	TBA